



SHE MULTI DRIVE

SHE MULTI DRIVE

Abseil-, Rettungshubgerät und Arbeitsgerät nach Maschinenrichtlinie (PAM)

geprüft und zugelassen nach

- Abseilgerät nach EN341:2011
max. Abseilhöhe (bis 2 Personen) 160m
Gerätekategorie A (100 kg)
Gerätekategorie B (200 kg)
- Rettungshubgerät nach EN1496:2017
max. Hubhöhe bis 160m
(*motorgetrieben*)
max. Hublast bis 200 kg
(*mittels Hubknarre*)
- Arbeitsgerät nach Maschinenrichtlinie 2006/42/EG
- Darf mit jedem Motorantrieb betrieben werden
- Hubfunktion manuell mit einer teleskopierbaren Hubratsche oder mittels Handrad
- Patentierte automatische Rücklaufsperre
- Absinkgeschwindigkeit 0,8m/s



All in One: Rettung und Seilarbeiten!



- | | |
|-------------------------------------|---|
| • <u>Antriebsarten</u> | elektrisch – pneumatisch – manuell |
| • <u>Retten und Befahren</u> | vollwertiges Rettungshub- & Befahrgerät |
| • <u>Sicherheit</u> | selbsthemmend (Rücklaufsperre),
Zugkraftbegrenzung,
jederzeit manuell bedienbar |
| • <u>Service</u> | wartungsarm, wartungsfreundlich |
| • <u>Nutzung</u> | minimaler Trainingsaufwand, einfache
Bedienung, schnelle, sichere Nutzung |

SICHER – EINFACH - VIELSEITIG



English
Version

SHE MULTI DRIVE

SHE MULTI DRIVE

Descender device with lifting function and working device according to the Machinery Directive (PAM)

Tested and approved according to

- Descender according to EN341:2011 max. Descending height (up to 2 persons) 160m Equipment class A (100 kg) Equipment class B (200 kg)
- Rescue lifting device according to EN1496:2017 max. Lifting height up to 160m (motor-driven) max. Lifting capacity up to 200 kg (by means of lifting ratchet)
- Working equipment according to Machinery Directive 2006/42/EC
- May be operated with any motor drive
- Manual lifting function with a telescopic lifting device or lifting ratchet or by means of handwheel
- Patented automatic backstop
- descent rate 0,8m/second



All in One: Rescue and rope work!



- | | |
|-------------------------------------|---|
| • <u>Types of drive</u> | electric – pneumatic – manual |
| • <u>Rescue and navigate</u> | vfull-fledged rescue lift & drive-in device |
| • <u>Collateral</u> | self-locking (return interlock),
Tractive effort limitation,
can be operated manually at any time |
| • <u>Service</u> | low-maintenance, easy to maintain |
| • <u>Utilization</u> | minimum training effort, simple
operation, fast and safe usage |

SAFE - SIMPLE - VERSATILE